

## Skid Steer Startup Shutdown

Date: \_\_\_\_\_ Time: \_\_\_\_\_ Operator/Inspector: \_\_\_\_\_  
 Serial Number: \_\_\_\_\_ Machine Hours: \_\_\_\_\_

For more information, please refer to the Operation and Maintenance Manual or any other applicable manuals and instructions.

Was procedure step completed properly?	✓	Remarks
<b>STARTING THE MACHINE...</b>		
Always perform a walk-around inspection	<input type="checkbox"/>	
Mount the machine using 3 points of contact	<input type="checkbox"/>	
Fasten seat belt	<input type="checkbox"/>	
Lower arm bars	<input type="checkbox"/>	
Make sure the joystick controls are in neutral	<input type="checkbox"/>	
Adjust the seat mounted joysticks to your comfort	<input type="checkbox"/>	
Set throttle to half throttle	<input type="checkbox"/>	
Make sure all implements are grounded	<input type="checkbox"/>	
Turn the key to start	<input type="checkbox"/>	
Leave throttle at half throttle during warm-up	<input type="checkbox"/>	
Select operating pattern (if equipped)	<input type="checkbox"/>	
Disengage parking brake	<input type="checkbox"/>	
<b>MACHINE WARM-UP...</b>		
Allow machine and hydrostatic system to warm-up	<input type="checkbox"/>	
Check instrument panels for any alert indicators	<input type="checkbox"/>	
Check hydraulics by raising lift arm	<input type="checkbox"/>	
Tilt quick coupler to cycle hydraulic oil	<input type="checkbox"/>	
Lower lift arms and tilt the quick coupler backward	<input type="checkbox"/>	
<b>MOVING THE MACHINE...</b>		
Make sure area is clear of personnel and obstructions	<input type="checkbox"/>	
Raise all lowered implements	<input type="checkbox"/>	
Move left joystick forward	<input type="checkbox"/>	
Move slowly as you move ahead	<input type="checkbox"/>	
<b>MACHINE SHUT DOWN...</b>		
Park machine on smooth, level area	<input type="checkbox"/>	
Lower lift arms, resting work tool firmly on the ground	<input type="checkbox"/>	
Allow machine to idle for a few minutes	<input type="checkbox"/>	
Turn engine off and remove key	<input type="checkbox"/>	
Face the machine and dismount machine using 3-point contact	<input type="checkbox"/>	
Conduct post-operation walk around inspection	<input type="checkbox"/>	

